

AWP04 Architectural Wall Pack

Power Selectable | 3CCT | 120-347V

Meet the successor to our AWP03 series Wall Packs, **now power and colour selectable!** Ideal for building entrances, multi-use facilities, apartment buildings, institutions, schools, and more



TECHNICAL DATA






LIGHT SPECIFICATIONS

| Lumens | 5,059 lm |
|----------|-------------------|
| Efficacy | 126.47 lm/W |
| CCT | 3000K/4000K/5000K |
| CRI | 72 |
| Dimmable | 0-10V |
| L70 Life | 50,000 hrs |
| Warranty | 10-year |


APPROVALS AND LISTINGS

| cETL | 5018387 |
|-------------|----------|
| DLC Premium | S-0W9LD6 |

DIMENSIONS



LUMINOUS INTENSITY DISTRIBUTION



ELECTRICAL

| Wattage | 10W/20W/30W/40W |
|----------------|-----------------|
| Voltage | 120-347V |
| Current | 0.45A |
| Power Factor | 0.9 |
| THD | 15% |
| Operating Temp | -30 to 45°C |

CONSTRUCTION

| Housing | Die-Cast Aluminum |
|-----------|-------------------|
| Lens | Polycarbonate |
| Finish | Bronze |
| IP Rating | IP65 |

DIMENSIONS AND WEIGHTS

| Fixture Weight | 3.5 lbs |
|--------------------|-------------------|
| Fixture Dimensions | 11 x 8.5 x 4.4 in |
| Carton Qty | 1 |
| Carton Weight | 4.2 lbs |
| Carton Dimensions | 13 x 9.6 x 5.9 in |

ACCESSORIES (Sold Separately)

| HD06VCRH | Photocell |
|-----------|-----------------------------|
| HD06-TUBE | Tube Extension for HD06VCRH |
| | (required) |
| HB01DMS-C | Motion Sensor |

